
Section 01 Identification

Product Identifier	ClearPAC 180 Series Clearpac 180, NSF® - 60 Clearpac 181, NSF® - 60 Clearpac 182, NSF® - 60
Other Means of Identification	Not available
Product Use and Restrictions on Use	Municipal potable water treatment
Initial Supplier Identifier	ClearTech Industries Inc 1500 Quebec Avenue Saskatoon, SK. Canada S7K 1V7 Phone: 800.387.7503 Fax: 888.281.8109 www.cleartech.ca
Prepared By	ClearTech Industries Inc. technical writer
24-Hour Emergency Phone	306.664.2522

Section 02 Hazard Identification

Physical Hazards

Corrosive to metals Category 1

Health Hazards

Serious eye damage / eye irritation Category 1

Signal Word

Danger

Hazard Statements

H290 May be corrosive to metals.

H318 Causes serious eye damage.

Pictograms



Precautionary Statements

Prevention

- P234 Keep only in original packaging.
- P264 Wash affected body parts thoroughly after handling.
- P280 Wear eye protection and face protection

Response

- P305 P351 P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
- P310
- P390 Absorb spillage to prevent material damage.

Hazards Not Otherwise Classified

Not available

Supplemental Information

Not available

Section 03 Composition / Information on Ingredients

Hazardous Ingredients:

Chemical name	Common name(s)	CAS number	Concentration (w/w%)
Aluminum chloride, basic	PAC; Poly Aluminum Chloride	1327-41-9	15-40%*

*Exact concentration withheld as a trade secret.

Section 04 First-Aid Measures

Description of necessary first-aid measures

- Inhalation** Get medical advice / attention if you feel unwell or are concerned.
- Ingestion** Get medical advice / attention if you feel unwell or are concerned.
- Skin contact** Rinse skin with lukewarm, gently flowing water / shower for 5 minutes or until product is removed. If skin irritation occurs or if you feel unwell: Get medical advice / attention.
- Eye contact** Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for 30 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately call a POISON CENTER or doctor.

Most important symptoms and effects, both acute and delayed

- Inhalation** May cause respiratory irritation.
- Ingestion** May cause discomfort or nausea.
- Skin contact** Not available
- Eye contact** Causes serious eye damage.
- Further information** For further information see Section 11 Toxicological Information.

Section 05 Fire Fighting Measures

- Suitable extinguishing media** Extinguish fire using extinguishing agents suitable for the surrounding fire.
- Unsuitable extinguishing media** Water jets are not recommended in fires involving chemicals.
- Specific hazards arising from the chemical** In the event of a fire oxides of aluminum and hydrogen chloride may be released.

Special protective equipment for fire-fighters Wear NIOSH-approved self-contained breathing apparatus and chemical-protective clothing.

Section 06 Accidental Release Measures

Personal Precautions / Protective Equipment / Emergency Procedures Wear appropriate personal protective equipment (See Section 08 Exposure Controls and Personal Protection). Stay upwind, ventilate area. Do not use material handling equipment with exposed metal surfaces.

Environmental Precautions Prevent material from entering waterways, sewers or confined spaces. Notify local health and wildlife officials. Notify operators of nearby water intakes.

Methods and Materials for Containment and Cleaning Up SMALL SPILLS: Stop or reduce leak if safe to do so. Clean up spill with non-reactive absorbent and place in suitable, covered, labeled containers. Flush area with water. Contaminated absorbent material may pose the same hazards as the spilled product. LARGE SPILLS: Contact fire and emergency services and supplier for advice.

Section 07 Handling and Storage

Precautions for Safe Handling Use proper equipment for lifting and transporting all containers. Use sensible industrial hygiene and housekeeping practices. Wash thoroughly after handling. Avoid all situations that could lead to harmful exposure.
Inspect containers for damage or leaks before handling. If the original label is damaged or missing replace with a workplace label. Have suitable emergency equipment for fires, spills and leaks readily available.

Conditions for Safe Storage Store in a cool, dry, well-ventilated area, away from heat sources and incompatible materials. Always store in original labeled container. Keep containers tightly closed when not in use and when empty. Empty containers may contain hazardous residues. Protect label and keep it visible. Do not transfer to metal containers.

Incompatibilities Strong acids, such as sulphuric, nitric, and hydrochloric.
Strong bases, such as potassium hydroxide, and sodium hydroxide.
Strong oxidizing agents, such as oxygen, hydrogen peroxide, hypochlorites and permanganates.
Metals, such as aluminum, steel, and brass.

Section 08 Exposure Controls and Personal Protection

Exposure limits

There are no known exposure limits for this product.

Engineering controls

Ventilation Requirements Mechanical ventilation (dilution or local exhaust), process or personnel enclosure and control of process conditions should be provided in accordance with all fire codes and regulatory requirements. Supply sufficient replacement air to make up for air removed by exhaust systems.

Other A soak hose and eyewash station or emergency shower and eyewash station should be available, tested, and be in close proximity to the product being handled in accordance with provincial regulations.

Protective equipment

The following are recommendations only. It is the responsibility of the employer / user to conduct a hazard assessment of the process in which this product being used and determine the proper engineering controls and PPE for their process. Additional regulatory and safety information should be sought from local authorities and, if needed, a professional industrial hygienist.

Eye and face protection	Where there is potential eye or face exposure, tightly fitting safety goggles and a face shield or a full face respirator or similar protective equipment which protects the wearer's face and eyes are recommended. Contact lenses are not recommended; they may contribute to severe eye injury.
Hand and body protection	Where handling this product it is recommended that skin contact is avoided.
Respiratory protection	In case of insufficient ventilation wear suitable respiratory equipment.
Thermal hazards	Not available

Section 09 Physical and Chemical Properties

Appearance

Physical state	Liquid
Colour	Pale yellow
Odour	Odourless
Odour threshold	Not applicable

Property

pH	<1.0
Melting point / freezing point	-20 °C
Initial boiling point and boiling range	105 °C
Flash point	Not applicable
Evaporation rate	Not available
Flammability	Not applicable
Upper flammable limit	Not available
Lower flammable limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	Not applicable
Solubility	Soluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available
Viscosity	Not available
Specific gravity	1.3-1.4 g/ml

Section 10 Stability and Reactivity

Reactivity	May be corrosive to metals.
Stability	This product is stable if stored according to the recommendations in Section 07.
Possibility of hazardous reactions	Hazardous polymerization is not known to occur.
Conditions to avoid	Avoid contact with incompatible materials. Do not freeze.
Incompatible materials	Strong acids, such as sulphuric, nitric, and hydrochloric. Strong bases, such as potassium hydroxide, and sodium hydroxide.

Strong oxidizing agents, such as oxygen, hydrogen peroxide, hypochlorites and permanganates.
Metals, such as aluminum, steel, and brass.

Hazardous decomposition products Thermal decomposition may produce oxides of aluminum and hydrogen chloride.

Section 11 Toxicological Information

Acute Toxicity (LD50 / LC50 values)

Component	Route	Species	Value	Exposure time
Aluminum chloride, basic	Oral	Rat	>2,000 mg/kg bw	
	Dermal	Rat	>2,000 mg/kg bw	

Toxic Health Effect Summary

Chemical characteristics	Aluminum chlorhydrate compounds are not readily absorbed by biological processes as they precipitate at neutral pH.
Skin	Not available
Ingestion	May cause discomfort or nausea.
Inhalation	May cause respiratory irritation.
Eye contact	Causes serious eye damage.
Sensitization	This product and its components at their listed concentration have no known sensitizing effects.
Mutagenicity	This product and its components at their listed concentration have no known mutagenic effects.
Carcinogenicity	This product and its components at their listed concentration have no known carcinogenic effects.
Reproductive toxicity	This product and its components at their listed concentration have no known reproductive effects.
Specific organ toxicity	This product and its components at their listed concentration have no known effects on specific organs.
Aspiration hazard	Not available
Synergistic materials	Not available

Section 12 Ecological Information

Ecotoxicity

there is no available toxicity data for this product.

Percentage of product with unknown environmental toxicity: 15-40%

Biodegradability	The domestic substance list categorizes aluminum chloride, basic as persistent.
Bioaccumulation	The domestic substance list categorizes aluminum chloride, basic as non-bioaccumulative.
Mobility	This product is water soluble, but is expected to adsorb to soil and is not expected to contaminate ground water.
Other adverse effects	The domestic substance list categorizes aluminum chloride, basic as inherently toxic to aquatic organisms.

Section 13 Disposal Considerations

Waste From Residues / Unused Products Dispose in accordance with all federal, provincial, and local regulations including the Canadian Environmental Protection Act.

Contaminated Packaging Do not remove label, follow label warnings even after the container is empty. Empty containers should be recycled or disposed of at an approved waste handling facility.

Section 14 Transport Information

UN number	UN3264
UN proper shipping name and description	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Polyaluminum chloride)
Transport hazard class(es)	8
Packing group	III
Excepted quantities	5L
Environmental hazards	Not listed as a marine pollutant under Canadian TDG Regulations, schedule III.
Special precautions	16 (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks).
Transport in bulk	ERAP index: not available MARPOL 73/78 and IBC Code: This product is not listed in Chapter 17 of the IBC Code.
Additional information	Secure containers (full or empty) during shipment and ensure all caps, valves, or closures are secured in the closed position.

TDG PRODUCT CLASSIFICATION: This product has been classified on the preparation date specified at section 16 of this SDS, for transportation in accordance with the requirements of part 2 of the Transportation of Dangerous Goods Regulations. If applicable, testing and published test data regarding the classification of this product are listed in the references at section 16 of this SDS.

Section 15 Regulatory Information.

NOTE: THE PRODUCT LISTED ON THIS SAFETY DATA SHEET HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CANADIAN HAZARDOUS PRODUCTS REGULATIONS. THIS SAFETY DATA SHEET CONTAINS ALL INFORMATION REQUIRED BY THOSE REGULATIONS.

All components of this product appear on the domestic substance list.

NSF Certification: ClearPAC 180 series is certified under NSF / ANSI Standard 60 for coagulation & flocculation at a maximum dosage of: 200 mg/L. NSF product use restrictions based on requirements obtained from the NSF website; consult NSF website for current requirements.

Section 16 Other Information

Date of latest revision: March 02, 2021

Note: The responsibility to provide a safe workplace remains with the buyer / user. The buyer / user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by the use of this material. It is the responsibility of the buyer / user to comply with all applicable laws and regulations regarding handling, using, reselling and shipping this product.

Attention: Receiver of the chemical goods / SDS coordinator

As part of our commitment to the RDC Responsible Distribution® initiative, ClearTech Industries Inc. and its associated companies require, as a condition of sale, that you forward the attached Safety Data Sheet(s) to all affected employees, customers, and end-users. ClearTech will send any available supplementary handling, health, and safety information to you at your request.

If you have any questions or concerns please call our customer service center.

References:

- 1) CHEMINFO
- 2) TOXNET
- 3) eChemPortal
- 4) ECHA
- 5) Transportation of Dangerous Goods Canada
- 6) HSDB
- 7) PAN