

Section 01 Identification

Product Identifier Hydrofluorosilicic Acid

Hydrofluorosilicic Acid, NSF® - 60

Other Means of Identification Hexafluorosilicic acid; Dihydrogen hexafluorosilicate; Fluorosilicic acid; Fluosilicic acid;

HFSA

Product Use and Restrictions Water fluoridation and wood preservation.

on Use

Initial Supplier Identifier ClearTech Industries Inc

1500 Quebec Avenue Saskatoon, SK. Canada

S7K 1V7

Phone: 800.387.7503 Fax: 888.281.8109 www.cleartech.ca

Prepared By ClearTech Industries Inc. technical writer

24-Hour Emergency Phone 306.664.2522

Section 02 Hazard Identification

Physical Hazards

Corrosive to metals Category 1

Health Hazards

Skin corrosion / irritation Category 1B Serious eye damage / eye Category 1

irritation

Signal Word

Danger

Hazard Statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Pictograms



Precautionary Statements

Prevention

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522

Revision Date: February 25, 2021

Page 1 of 8

P234 Keep only in original packaging.

P260 Do not breathe vapours, fumes, or mists.

P264 Wash affected body parts thoroughly after handling.

P280 Wear protective gloves, protective clothing, eye protection, face protection

Response

P301 P330 P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 P361 P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

P363 shower. Wash contaminated clothing before reuse.

P304 P340 P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a

POISON CENTER or doctor.

P305 P351 P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P390 Absorb spillage to prevent material damage.

Storage

P405 Store locked up.

Disposal

P501 Dispose of contents / container in accordance with all federal, provincial and / or local regulations including the Canadian Environmental Protection Act.

Hazards Not Otherwise Classified

Not available

Supplemental Information

Not available

Section 03 Composition / Information on Ingredients

Hazardous Ingredients:

Chemical name	Common name(s)	CAS number	Concentration (w/w%)
Silicate(2-), hexafluoro-, dihydrogen	Hydrofluorosilicic acid (HFSA)	16961-83-4	≥22%
Hydrogen flouride	HF	7664-39-3	0.1-1.0%

Section 04 First-Aid Measures

Description of necessary first-aid measures

Inhalation Remove source of exposure or move person to fresh air and keep comfortable for breathing. Call a POISON

CENTER or doctor. If breathing has stopped, trained personnel should begin rescue breathing or if the heart has stopped, immediately start cardiopulmonary resuscitation (CPR) or automated external defibrillation

(AED). Avoid mouth to mouth contact by using a barrier device.

Ingestion Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. If vomiting occurs

naturally, lie on your side, in the recovery position.

Skin Avoid direct contact. Wear chemical protective clothing, if necessary. Take off immediately contaminated contact clothing, shoes and leather goods. Rinse skin with lukewarm, gently flowing water / shower for 30 minutes.

Immediately call a POISON CENTER or doctor. Wash contaminated clothing before re-use, or discard.

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Revision Date: February 25, 2021

Eye contact Avoid direct contact. Wear chemical protective gloves, if necessary. Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for 30 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately call a POISON CENTER or doctor.

Most important symptoms and effects, both acute and delayed

Inhalation Causes severe burns to the mouth and throat (mist).

Ingestion Causes burns to the mouth and throat.

Skin contact Causes severe skin burns. Eye contact Causes serious eye damage.

Further information For further information see Section 11 Toxicological Information.

Section 05 Fire Fighting Measures

Suitable extinguishing media Extinguish fire using extinguishing agents suitable for the surrounding fire.

Unsuitable extinguishing media

the chemical

Water jets are not recommended in fires involving chemicals.

Specific hazards arising from

Reacts with many metals to liberate hydrogen gas that can form explosive mixtures.

Thermal decomposition occurs at 105 °C. In the event of a fire toxic and corrosive fumes of

hydrogen flouride and silicon tetrafluoride may be released.

Special protective equipment

for fire-fighters

Wear NIOSH-approved self-contained breathing apparatus and chemical-protective

clothing.

Section 06 Accidental Release Measures

Personal Precautions / Protective Equipment / **Emergency Procedures** Wear appropriate personal protective equipment (See Section 08 Exposure Controls and Personal Protection). Stay upwind, ventilate area. Do not breathe vapours, fumes, or mists.

Do not use material handling equipment with exposed metal surfaces.

Environmental Precautions

Prevent material from entering waterways, sewers or confined spaces. Notify local health

and wildlife officials. Notify operators of nearby water intakes.

vented containers to avoid pressure buildup.

Methods and Materials for Containment and Cleaning Up

SMALL SPILLS: Stop or reduce leak if safe to do so. Clean up spill with non-reactive absorbent and place in suitable, covered, labeled containers. Flush area with water. Contaminated absorbent material may pose the same hazards as the spilled product. Use

LARGE SPILLS: Contact fire and emergency services and supplier for advice.

Section 07 Handling and Storage

Precautions for Safe Handling Use proper equipment for lifting and transporting all containers. Use sensible industrial hygiene and housekeeping practices. Wash thoroughly after handling. Avoid all situations that could lead to harmful exposure. Prevent the release of vapours, fumes, or mists into the workplace air.

> Inspect containers for damage or leaks before handling. If the original label is damaged or missing replace with a workplace label. Have suitable emergency equipment for fires, spills and leaks readily available.

Never return contaminated material to its original container.

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Revision Date: February 25, 2021 Page 3 of 8

Conditions for Safe Storage Store in a cool, dry, well-ventilated area, away from heat sources and incompatible

materials. Always store in original labeled container. Keep containers tightly closed when not in use and when empty. Empty containers may contain hazardous residues. Protect label and keep it visible. Do not transfer to metal containers. Do not transfer to glass,

concrete or stoneware containers.

Incompatibilities Bases, such as potassium hydroxide, sodium hydroxide, calcium hydroxide (slaked lime),

ammonia, carbonates.

Metals, such as aluminum, steel, and brass. Silicates, such as glass, sand, and fiberglass.

Strong, concentrated acids, such as sulphuric, hydrochloric or nitric.

Section 08 Exposure Controls and Personal Protection

Exposure limits

Component	Regulation	Type of listing	Value
Hydrogen fluoride	NIOSH	REL-TWA	3 ppm (2.5 mg/m³)
	NIOSH	STEL/Ceiling	6 ppm (5 mg/m³)
	NIOSH	IDLH	30 ppm (25 mg/m³)
	OSHA	PEL	3 ppm (2.5 mg/m³)
Fluorides (as F)	ACGIH	TWA	2.5 mg/m ³

Engineering controls

Ventilation Requirements Mechanical ventilation (dilution or local exhaust), process or personnel enclosure and

control of process conditions should be provided in accordance with all fire codes and regulatory requirements. Supply sufficient replacement air to make up for air removed by

exhaust systems.

Other An emergency shower and eyewash station should be available, tested, and be in close

proximity to the product being handled in accordance with provincial regulations.

Protective equipment

Revision Date: February 25, 2021

The following are recommendations only. It is the responsibility of the employer / user to conduct a hazard assessment of the process in which this product being used and determine the proper engineering controls and PPE for their process. Additional regulatory and safety information should be sought from local authorities and, if needed, a professional industrial hygienist.

Eye and face protection Where there is potential eye or face exposure, tightly fitting safety goggles and a face shield

or a full face respirator or similar protective equipment which protects the wearer's face and eyes are recommended. Contact lenses are not recommended; they may contribute to

severe eye injury.

Hand and body protection Disposable latex or nitrile gloves are recommended to prevent incidental contact. Butyl

rubber, neoprene, or PVC skin protection is recommended for extended contact. Leather

gloves are not recommended for chemical protection. Refer to manufacturer's

specifications for breakthrough times and permeability information; note that breakthrough times and permeability vary with temperature, application and age of material. Continued use of contaminated safety gear or clothing is not recommended; wash before reuse or

discard.

Respiratory protection In case of insufficient ventilation wear suitable respiratory equipment.

NIOSH respirator recommendations for: Hydrogen Flouride

Up to: 30 ppm (25 mg/m³)

Customer Service: 800.387.7503 <u>www.cleartech.ca</u> Emergency: 306.664.2522

(APF = 10) Any chemical cartridge respirator with cartridge(s) providing protection against Hydrogen Flouride

(APF = 10) Any supplied-air respirator

(APF = 25) Any powered, air-purifying respirator with cartridge(s) providing protection against Hydrogen Flouride

(APF = 50) Any air-purifying, full-facepiece respirator (gas mask) with a chin-style, front- or back-mounted canister providing protection against Hydrogen Flouride

(APF = 50) Any self-contained breathing apparatus with a full facepiece.

Emergency or planned entry into unknown concentrations or IDLH conditions:

(APF = 10,000) Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode

(APF = 10,000) Any supplied-air respirator that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained positive-pressure breathing apparatus

Escape:

Any appropriate escape-type, self-contained breathing apparatus

Thermal hazards Not available

Section 09 Physical and Chemical Properties

Appearance

Physical state Liquid

Colour Colourless to pale yellow

Odour Sour, pungent Odour threshold Not available

Property

pH ~1.0 Melting point / freezing point -15 °C Initial boiling point and 105 °C

boiling range

Flash point Not available
Evaporation rate Not available
Flammability Not applicable
Upper flammable limit Not available
Lower flammable limit Not available

Vapour pressure ~3 kPa or 20 mmHg

Vapour densityNot availableRelative densityNot applicableSolubilitySoluble in waterPartition coefficient: n-Not available

octanol/water

Auto-ignition temperature Not available

Decomposition temperature 105 °C

Revision Date: February 25, 2021

Viscosity Not available

Customer Service: 800.387.7503 <u>www.cleartech.ca</u> Emergency: 306.664.2522

Specific gravity 1.197 @ 15.6 °C

Formula H₂SiF₆ Molecular weight 144.091 g/mol

Section 10 Stability and Reactivity

Reactivity May be corrosive to metals. Reacts with many metals to liberate hydrogen gas that can

form explosive mixtures. Reacts violently with bases.

Stability This product is stable if stored according to the recommendations in Section 07.

Possibility of hazardous

reactions

Hazardous polymerization is not known to occur.

Conditions to avoid Avoid contact with incompatible materials. Do not heat.

Incompatible materials Bases, such as potassium hydroxide, sodium hydroxide, calcium hydroxide (slaked lime),

ammonia, carbonates.

Metals, such as aluminum, steel, and brass. Silicates, such as glass, sand, and fiberglass.

Strong, concentrated acids, such as sulphuric, hydrochloric or nitric.

Hazardous decomposition

products

Thermal decomposition may produce toxic and corrosive fumes of hydrogen flouride and

silicon tetrafluoride.

Section 11 Toxicological Information

Acute Toxicity (LD50 / LC50 values)

There is no available toxicity data for this product.

Toxic Health Effect Summary

Chemical When hydrofluorosilicic acid is neutralized it releases highly reactive hydrogen fluoride.

characteristics

Skin

Causes severe skin burns.

Causes burns to the mouth and throat. Ingestion

Inhalation Causes severe burns to the mouth and throat (mist).

Eye contact Causes serious eye damage.

Sensitization This product and its components at their listed concentration have no known sensitizing effects. Mutagenicity This product and its components at their listed concentration have no known mutagenic effects.

ACGIH has classified hydrofluorosilicic acid as category A4 - Not classifiable as a human carcinogen. Carcinogenicity

Reproductive toxicity

This product and its components at their listed concentration have no known reproductive effects.

Specific organ

This product and its components at their listed concentration have no known effects on specific

organs.

Not available Aspiration hazard

Synergistic materials

toxicity

Product has a strong affinity for calcium and magnesium: increasing calcification of bones and

reducing calcium and magnesium levels in the blood.

Section 12 Ecological Information

Ecotoxicity

Percentage of product with unknown environmental toxicity: 22%

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Revision Date: February 25, 2021

Page 6 of 8

Component	Туре	Species	Value	Exposure Time
Hydrofluorosilicic acid	LC50	Freshwater fish	50 mg/L	96 hours
Fluoride	EC50	Aquatic invertabrates	26-48 mg/L	48 hours
Sodium fluoride	EC50	Freshwater algea	43-122 mg/L	72 hours

Biodegradability The domestic substance list categorizes all of the components of this product as

persistent.

Bioaccumulation The domestic substance list categorizes all of the components of this product as non-

bioaccumulative.

Mobility This product is water soluble, but is expected to adsorb to soil and is not expected to

contaminate ground water.

Other adverse effects Not available

Section 13 Disposal Considerations

Waste From Residues /

Unused Products

Dispose in accordance with all federal, provincial, and local regulations including the

Canadian Environmental Protection Act.

Contaminated Packaging Do not remove label, follow label warnings even after the container is empty. Empty

containers should be recycled or disposed of at an approved waste handling facility.

Section 14 Transport Information

UN number **UN1778**

UN proper shipping name

and description

FLUOROSILICIC ACID

Transport hazard class(es) 8 Ш Packing group **Excepted quantities** 1 L

Environmental hazards

Not listed as a marine pollutant under Canadian TDG Regulations, schedule III.

Special precautions No special provisions

Transport in bulk

ERAP index: not available

MARPOL 73/78 and IBC Code:

Product name: Fluorosilicic acid (20-30%) in water solution

Pollution category: Y

Hazards: the product is included in the Code because of both its safety

and pollution hazards.

Ship type: ship type 3

Tank type: independent gravity tank

Tank vents: controlled venting

Tank environmental control: no special requirements under this Code

Temperature classes no requirements

Electrical equipment: Apparatus group no requirements

> Flash point non-flammable product

Gauging: restricted gauging Vapour detection: toxic vapours

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Revision Date: February 25, 2021

Fire protection: no special requirements under this Code

Emergency equipment see 14.3.1

Specific and operational 15.11, 15.19.6 requirements

Additional information

Secure containers (full or empty) during shipment and ensure all caps, valves, or closures are secured in the closed position.

TDG PRODUCT CLASSIFICATION: This product has been classified on the preparation date specified at section 16 of this SDS, for transportation in accordance with the requirements of part 2 of the Transportation of Dangerous Goods Regulations. If applicable, testing and published test data regarding the classification of this product are listed in the references at section 16 of this SDS.

Section 15 Regulatory Information.

NOTE: THE PRODUCT LISTED ON THIS SAFETY DATA SHEET HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CANADIAN HAZARDOUS PRODUCTS REGULATIONS. THIS SAFETY DATA SHEET CONTAINS ALL INFORMATION REQUIRED BY THOSE REGULATIONS.

All components of this product appear on the domestic substance list.

NSF Certification: Hydrofluorosilicic Acid, NSF® - 60 is certified under NSF / ANSI Standard 60 for fluoridation at a maximum dosage of: 5 mg/L. NSF product use restrictions based on requirements obtained from the NSF website; consult NSF website for current requirements.

Section 16 Other Information

Date of latest revision: February 25, 2021

Note: The responsibility to provide a safe workplace remains with the buyer / user. The buyer / user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by the use of this material. It is the responsibility of the buyer / user to comply with all applicable laws and regulations regarding handling, using, reselling and shipping this product.

Attention: Receiver of the chemical goods / SDS coordinator

As part of our commitment to the RDC Responsible Distribution® initiative, ClearTech Industries Inc. and its associated companies require, as a condition of sale, that you forward the attached Safety Data Sheet(s) to all affected employees, customers, and end-users. ClearTech will send any available supplementary handling, health, and safety information to you at your request.

If you have any questions or concerns please call our customer service center.

References:

- 1) CHEMINFO
- 2) TOXNET
- 3) eChemPortal
- 4) ECHA
- 5) Transportation of Dangerous Goods Canada
- 6) HSDB
- 7) PAN

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Revision Date: February 25, 2021 Page 8 of 8