

Section 01 Identification

Product Identifier	Sodium Bisulphite 35-40% Solution Sodium Bisulphite 35% Solution Sodium Bisulphite 38% Solution Sodium Bisulphite 38% Solution, NSF® - 60 Sodium Bisulphite 40% Solution NSF Grade
Other Means of Identification	Sodium hydrogensulphite
Product Use and Restrictions on Use	Oxygen scavenger, reducing agent, dechlorination, photochemicals, bleaching agent, and papermaking. This product is NSF certified for use in drinking water, see section 15 and the NSF website for further information.
Initial Supplier Identifier	ClearTech Industries Inc. 1500 Quebec Avenue Saskatoon, SK. Canada S7K 1V7 Phone: 800.387.7503 Fax: 888.281.8109 www.cleartech.ca
Prepared By	ClearTech Industries Inc. technical writer
24-Hour Emergency Phone	306.664.2522

Section 02 Hazard Identification

Physical Hazards

Corrosive to metals Category 1

Health Hazards

Serious eye damage / eye irritation Category 2

Signal Word

Warning

Hazard Statements

H290 May be corrosive to metals.

H319 Causes serious eye irritation.

Pictograms



Precautionary Statements

Prevention

- P234 Keep only in original packaging.
P264 Wash affected body parts thoroughly after handling.
P280 Wear protective gloves/eye protection, face protection.

Response

- P305 P351 P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
P390 Absorb spillage to prevent material damage.

Hazards Not Otherwise Classified

Contact with acids liberates toxic gas.

Supplemental Information

Not available

Section 03 Composition / Information on Ingredients

Hazardous Ingredients:

Chemical name	Common name(s)	CAS number	Concentration (w/w%)
Sodium hydrogensulphite	Sodium bisulphite	7631-90-5	33-42%

Section 04 First-Aid Measures

Description of necessary first-aid measures

- Inhalation** Get medical advice / attention if you feel unwell or are concerned.
- Ingestion** Get medical advice / attention if you feel unwell or are concerned.
- Skin contact** Rinse skin with lukewarm, gently flowing water / shower for 5 minutes or until product is removed. If skin irritation occurs or if you feel unwell: Get medical advice / attention.
- Eye contact** Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for 15 to 20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice / attention.

Most important symptoms and effects, both acute and delayed

- Inhalation** May cause respiratory irritation. Contact with acids, heat or sunlight releases sulphur dioxide, which causes serious respiratory irritation and is toxic if inhaled.
- Ingestion** May cause discomfort or nausea. This product may provoke a response in those who are sensitive to sulphites.
- Skin contact** This product may provoke a response in those who are sensitive to sulphites.
- Eye contact** Causes serious eye irritation.
- Further information** For further information see Section 11 Toxicological Information.

Section 05 Fire Fighting Measures

- Suitable extinguishing media** Extinguish fire using extinguishing agents suitable for the surrounding fire.
- Unsuitable extinguishing media** Water jets are not recommended in fires involving chemicals.

Specific hazards arising from the chemical	In the event of a fire oxides of sulphur may be released. Thermal decomposition occurs at 150 °C.
Special protective equipment for fire-fighters	Wear NIOSH-approved self-contained breathing apparatus and chemical-protective clothing.

Section 06 Accidental Release Measures

Personal Precautions / Protective Equipment / Emergency Procedures	Wear appropriate personal protective equipment (See Section 08 Exposure Controls and Personal Protection). Stay upwind, ventilate area. Do not use material handling equipment with exposed metal surfaces.
Environmental Precautions	Prevent material from entering waterways, sewers or confined spaces. Notify local health and wildlife officials. Notify operators of nearby water intakes.
Methods and Materials for Containment and Cleaning Up	SMALL SPILLS: Stop or reduce leak if safe to do so. Clean up spill with non-reactive absorbent and place in suitable, covered, labeled containers. Flush area with water. Contaminated absorbent material may pose the same hazards as the spilled product. Use vented containers to avoid pressure buildup. LARGE SPILLS: Contact fire and emergency services and supplier for advice.

Section 07 Handling and Storage

Precautions for Safe Handling	Use proper equipment for lifting and transporting all containers. Use sensible industrial hygiene and housekeeping practices. Wash thoroughly after handling. Avoid all situations that could lead to harmful exposure. Inspect containers for damage or leaks before handling. If the original label is damaged or missing replace with a workplace label. Have suitable emergency equipment for fires, spills and leaks readily available. Never return contaminated material to its original container.
Conditions for Safe Storage	Store in a cool, dry, well-ventilated area, away from heat sources and incompatible materials. Always store in original labeled container. Keep containers tightly closed when not in use and when empty. Empty containers may contain hazardous residues. Protect label and keep it visible. Do not transfer to metal containers.
Incompatibilities	Acids, such as sulphuric, nitric, hydrochloric, phosphoric, fluosilicic (HFSA), sulphonic, acetic, citric, oxalic, and formic. Oxidizing agents, such as oxygen, hydrogen peroxide, sulphuric and nitric acids, hypochlorites and permanganates. Metals, such as aluminum, carbon steel, and brass.

Section 08 Exposure Controls and Personal Protection

Exposure limits

Component	Regulation	Type of listing	Value
Sulphur dioxide	ACGIH	TWA	2 ppm (5 mg/m ³)
		STEL/Ceiling	5 ppm (13 mg/m ³)

Engineering controls

Ventilation Requirements	Mechanical ventilation (dilution or local exhaust), process or personnel enclosure and control of process conditions should be provided in accordance with all fire codes and regulatory requirements. Supply sufficient replacement air to make up for air removed by exhaust systems.
Other	An eye wash bottle or eye wash station should be available, tested, and be in close proximity to the product being handled in accordance with provincial regulations.

Protective equipment

The following are recommendations only. It is the responsibility of the employer / user to conduct a hazard assessment of the process in which this product being used and determine the proper engineering controls and PPE for their process. Additional regulatory and safety information should be sought from local authorities and, if needed, a professional industrial hygienist.

Eye and face protection	Where there is potential eye or face exposure, tightly fitting chemical goggles are recommended. Contact lenses are not recommended; they may contribute to severe eye injury.
Hand and body protection	Where handling this product it is recommended that skin contact is avoided.
Respiratory protection	In case of insufficient ventilation wear suitable respiratory equipment.

NIOSH respirator recommendations for: Sulphur dioxide

Up to: 20 ppm

(APF = 10) Any chemical cartridge respirator with cartridge(s) providing protection against Sulphur dioxide

(APF = 10) Any supplied-air respirator

Up to: 50 ppm

(APF = 25) Any supplied-air respirator operated in a continuous-flow mode

(APF = 25) Any powered, air-purifying respirator with cartridge(s) providing protection against Sulphur dioxide

Up to: 100 ppm

(APF = 50) Any chemical cartridge respirator with a full facepiece and cartridge(s) providing protection against Sulphur dioxide

(APF = 50) Any air-purifying, full-facepiece respirator (gas mask) with a chin-style, front- or back-mounted canister providing protection against Sulphur dioxide

(APF = 50) Any self-contained breathing apparatus with a full facepiece.

(APF = 50) Any supplied-air respirator with a full facepiece

Emergency or planned entry into unknown concentrations or IDLH conditions:

(APF = 10,000) Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode

(APF = 10,000) Any supplied-air respirator that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained positive-pressure breathing apparatus

Escape:

(APF = 50) Any air-purifying, full-facepiece respirator (gas mask) with a chin-style, front- or back-mounted canister providing protection against Sulphur dioxide

Thermal hazards Not available

Section 09 Physical and Chemical Properties

Appearance

Physical state	Liquid
Colour	Clear, colourless to pale yellow
Odour	Sulphurous
Odour threshold	Not available

Property

Safety Data Sheet

Sodium Bisulphite 35-40% Solution
ClearTech Industries Inc

pH	~4.0
Melting point / freezing point	6 °C
Initial boiling point and boiling range	104 °C
Flash point	Not applicable
Evaporation rate	Not available
Flammability	Not applicable
Upper flammable limit	Not available
Lower flammable limit	Not available
Vapour pressure	10.4 kPa @ 20°C
Vapour density	Not available
Relative density	Not applicable
Solubility	Soluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	150 °C
Viscosity	Not available
Specific gravity	1.29-1.35
Particle characteristics	Not applicable
Formula	NaHSO ₃
Molecular weight	104.06 g/mol

Section 10 Stability and Reactivity

Reactivity	May be corrosive to metals. Reacts with acids to form toxic and corrosive sulphur dioxide.
Stability	This product is stable if stored according to the recommendations in Section 07. Exposure to sunlight or high temperatures may cause the degradation of this product over time.
Possibility of hazardous reactions	Hazardous polymerization is not known to occur.
Conditions to avoid	Avoid contact with incompatible materials. Do not heat. Do not freeze.
Incompatible materials	Acids, such as sulphuric, nitric, hydrochloric, phosphoric, fluoro-silicic (HFSA), sulphonic, acetic, citric, oxalic, and formic. Oxidizing agents, such as oxygen, hydrogen peroxide, sulphuric and nitric acids, hypochlorites and permanganates. Metals, such as aluminum, carbon steel, and brass.
Hazardous decomposition products	Thermal decomposition may produce oxides of sulphur. Thermal decomposition occurs at 150 °C.

Section 11 Toxicological Information

Acute Toxicity (LD50 / LC50 values)

Component	Route	Species	Value	Exposure time
Sodium bisulphite	Oral	Rat	2160 mg/kg	
	Dermal	Rat	>2000 mg/kg	

Toxic Health Effect Summary

Customer Service: 800.387.7503
Revision Date: July 31, 2024

www.cleartech.ca

Emergency: 306.664.2522

Page 5 of 8

Safety Data Sheet

Sodium Bisulphite 35-40% Solution
ClearTech Industries Inc

Chemical characteristics	This chemical is a moderate reducing agent.
Skin	This product may provoke a response in those who are sensitive to sulphites.
Ingestion	May cause discomfort or nausea. This product may provoke a response in those who are sensitive to sulphites.
Inhalation	May cause respiratory irritation. Contact with acids, heat or sunlight releases sulphur dioxide, which causes serious respiratory irritation and is toxic if inhaled.
Eye contact	Causes serious eye irritation.
Sensitization	This product may provoke a response in those who are sensitive to sulphites.
Mutagenicity	This product and its components at their listed concentration have no known mutagenic effects.
Carcinogenicity	This product and its components at their listed concentration have no known carcinogenic effects.
Reproductive toxicity	This product and its components at their listed concentration have no known reproductive effects.
Specific organ toxicity	This product and its components at their listed concentration have no known effects on specific organs.
Aspiration hazard	Not available
Synergistic materials	Not available

Section 12 Ecological Information

Ecotoxicity

Component	Type	Species	Value	Exposure Time
Sodium bisulphite	EC50	Daphnia	>100 mg/L	48 hours
	LC50	Fish	>100 mg/L	96 hours
	EC50	Algae	65 mg/L	72 hours

Biodegradability	The domestic substance list categorizes sodium bisulphite as persistent.
Bioaccumulation	The domestic substance list categorizes sodium bisulphite as non-bioaccumulative.
Mobility	This product is water soluble, is not predicted to adsorb to soil and may contaminate ground water.
Other adverse effects	Absorbs oxygen from aquatic environments.

Section 13 Disposal Considerations

Waste From Residues / Unused Products	Dispose in accordance with all federal, provincial, and local regulations including the Canadian Environmental Protection Act.
Contaminated Packaging	Do not remove label, follow label warnings even after the container is empty. Empty containers should be recycled or disposed of at an approved waste handling facility.

Section 14 Transport Information

UN number	UN2693
UN proper shipping name and description	BISULPHITES, AQUEOUS SOLUTION, N.O.S. (Sodium Bisulphite)
Transport hazard class(es)	8
Packing group	III

Excepted quantities	5 L
Environmental hazards	Not listed as a marine pollutant under Canadian TDG Regulations, schedule III.
Special precautions	
Transport in bulk	ERAP index: not available
Additional information	<p>MARPOL 73/78 and IBC Code: This product is not listed in Chapter 17 of the IBC Code.</p> <p>Secure containers (full or empty) during shipment and ensure all caps, valves, or closures are secured in the closed position.</p> <p>Special Provisions:</p> <p>16 (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks).</p>

TDG PRODUCT CLASSIFICATION: This product has been classified on the preparation date specified at section 16 of this SDS, for transportation in accordance with the requirements of part 2 of the Transportation of Dangerous Goods Regulations. If applicable, testing and published test data regarding the classification of this product are listed in the references at section 16 of this SDS.

Section 15 Regulatory Information.

NOTE: THE PRODUCT LISTED ON THIS SAFETY DATA SHEET HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CANADIAN HAZARDOUS PRODUCTS REGULATIONS. THIS SAFETY DATA SHEET CONTAINS ALL INFORMATION REQUIRED BY THOSE REGULATIONS.

All components of this product appear on the domestic substance list.

NSF Certification: Sodium Bisulphite 38% is certified under NSF / ANSI / CAN 60 for dechlorination and as an antioxidant at a maximum dosage of: 50 mg/L. NSF product use restrictions based on requirements obtained from the NSF website; consult NSF website for current requirements.

Section 16 Other Information

Date of latest revision: July 31, 2024

Note: The responsibility to provide a safe workplace remains with the buyer / user. The buyer / user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by the use of this material. It is the responsibility of the buyer / user to comply with all applicable laws and regulations regarding handling, using, reselling and shipping this product.

Attention: Receiver of the chemical goods / SDS coordinator

As part of our commitment to the RDC Responsible Distribution® initiative, ClearTech Industries Inc. and its associated companies require, as a condition of sale, that you forward the attached Safety Data Sheet(s) to all affected employees, customers, and end-users. ClearTech will send any available supplementary handling, health, and safety information to you at your request.

If you have any questions or concerns please call our customer service center.

References:

- 1) *NIOSH Pocket Guide to Chemical Hazards*; U.S. Department of Health and Human Services, <https://www.cdc.gov/niosh/npg/default.html>
- 2) *WorkSafe BC E-Limit*; Workers' Compensation Board of British Columbia, <https://elimit.online.worksafebc.com/>
- 3) *ECHA - Registered Substance Dossier*; European Chemicals Agency, <https://echa.europa.eu/registration-dossier/-/registered-dossier/15334>
- 4) *Transportation of Dangerous Goods Regulations*; Transport Canada, <https://laws-lois.justice.gc.ca/eng/regulations/SOR-2001-286/index.html>
- 5) Globally Harmonized System of Classification and Labeling of Chemicals (GHS) *Seventh revised edition*
- 6) International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk (IBC Code) 2007 Edition
- 7) The ACS Style Guide